


## Data Sheet

# Monolithic Ceramic Capacitors

## GCM2165C1H180JZ13□ (0805, C0G, 18pF, 50Vdc)

□: packaging code

RoHS regulation conformity parts



(in mm)

**Dimensions**

Length L	2.0mm±0.15mm
Width W	1.25mm±0.15mm
Thickness T	0.6mm±0.1mm
Electrode e	0.2 to 0.7mm
Electrode Gap g (min.)	0.7mm

**Rated Value**

	Murata PN Code	Spec
Temperature Char.	<b>5C</b>	C0G (EIA), 0±30ppm/°C
Capacitance	<b>180</b>	18pF
Capacitance Change	<b>J</b>	±5%
Rated Voltage	<b>1H</b>	50Vdc

**Packaging**

Code	Packaging	Minimum Quantity
<b>D</b>	180mm Paper Tape	4000
<b>J</b>	330mm Paper Tape	10000
<b>C</b>	Bulk Case	10000
<b>B</b>	Bulk(Bag)	1000

**Specifications**

Please refer to  
'GCM Series Specification and Test Methods'  
PDF file.

GCM Series meets AEC-Q200 requirements.

● This data sheet is applied for CHIP MONOLITHIC CERAMIC CAPACITOR used for Automotive (For Power-train, Safety equipments) Electronics equipment for your design.

**<Notice>**

● Solderability of Tin plating termination chip might be deteriorated when low temperature soldering profile where peak solder temperature is below the Tin melting point is used. Please confirm the solderability of Tin plating termination chip before use.

• The RoHS compliance means that we judge from EU Directive 2002/95/EC the products do not contain lead, cadmium, mercury, hexavalent chromium, PBB and PBDE, except exemptions stated in EU Directive 2002/95/EC annex and impurities existing in natural world.

• This statement does not insure the compliance of any of the listed parts with any laws or legal imperatives developed by any EU members individually with regards to the RoHS Directive.

**⚠ Note:**

1. This datasheet is downloaded from the website of Murata Manufacturing co., ltd. Therefore, its specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2. This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please approve our product specifications or transact the approval sheet for product specifications before ordering.