
	THE REVISION STATUS OF ALL SHEETS OF THIS DRAWING IS THE SAME AS SHEET 1						
REV	REV DESCRIPTION DATE BY						
Α	INITIAL RELEASE	10/28/22	YA				



Dwg. Number	Customer P/N	Customer P/N Times P/N		
IE-00418-01	-	IBPS092-SMSM-6.0IN	6 +0.20/-0	
IE-00418-02	-	IBPS092-SMSM-8.0IN	8 +0.20/-0	
IE-00418-03	-	IBPS092-SMSM-10.0IN	10 +0.20/-0	
IE-00418-04	-	IBPS092-SMSM-12.0IN	12 +0.24/-0	

1.0 Scope

This drawing documents the construction and performance of PT- 092 cable assemblies manufactured by Times Microwave systems.

2.0 Cable Information

- 2.1 Cable to be PT-092
- 2.2 Jacket color to be Black
- 2.3 Jacket material to be Tefzel
- 2.4 Nominal cable impedance to be 50 ohms
- 2.5 Cable diameter to be 0.101" [2.57mm] (Nominal).

3.0 Connector Information

3.1 Forward Connector

Type SMA (M) Straight Connector (SP150) Connector Body – Stainless Steel, Gold Plated Center Contact – Beryllium Copper, Gold Plated

3.2 After Connector

Type SMA (M) Straight Connector (SP150) Connector Body – Stainless Steel, Gold Plated Center Contact – Beryllium Copper, Gold Plated

Unless otherwise specified, dimensions are in INCH. Tolerances are applicable when specified.		prova	als	TIMES MICROWAVE				VAVE SYSTEMS
	Drawn	YA	10/28/22		II		www.timesmicrowave.com	
These drawings and specifications contain proprietary information	Checked			PT-092 CABLE ASSEMBLY (Space Assemblies)				
which is the property of	Approved					blies)		
i imes iviicrowave	Approved	pproved		Size	CAGE C	CODE	Drawing	No.:
Systems.				Α	6899	99	IE.	-00418-XX
				Scale:	NA	Rev.	(A)	Sheet: 1 of 3

	THE REVISION STATUS OF ALL SHEETS OF THIS DRAWING IS THE SAME AS SHEET 1								
REV DESCRIPTION DATE BY									
Α	INITIAL RELEASE	10/28/22	YA						

4.0 Electrical Performance

- 4.1 Frequency range: DC 27GHz
- 4.2 Insertion loss & VSWR: As per below table,

Dwg. Number	Max. Insertion Loss in dB	Max. VSWR		
Dwg. Number	@ 27GHz	@ 27GHz		
IE-00418-01	1.06	1.35		
IE-00418-02	1.29	1.35		
IE-00418-03	1.53	1.35		
IE-00418-04	1.76	1.35		

5.0 Mechanical Performance

- 5.1 Overall Length to be specified length.
- 5.2 Minimum Bend radius is 0.437" [11.1mm].

6.0 Environmental Performance

- 6.1 Installation Temperature Range (-65°C to +150°C)
- 6.2 Storage Temperature Range (-65°C to +150°C)
- 6.3 Operating Temperature Range (-65°C to +150°C)

7.0 Marking

- 7.1 Markers are to be black text on White Color Marker Sleeve.
- 7.2 Marker Configuration to be:

Dwg. Number	Marker 1
IE-00418-01	Times Microwave Systems IBPS092-SMSM-6.0IN \$\$\$\$\$
IE-00418-02	Times Microwave Systems IBPS092-SMSM-8.0IN \$\$\$\$\$
IE-00418-03	Times Microwave Systems IBPS092-SMSM-10.0IN \$\$\$\$\$

Unless otherwise specified, dimensions are in INCH. Tolerances are applicable when spec-				TIMES MICROWAVE SYSTEMS					
liei i i	Drawn	YA	10/28/22		www.timesmicrowave.com			crowave.com	
These drawings and specifications contain proprietary information	Checked			PT-092 CABLE ASSEMBLY				_	
Trade de la companya	Approved				(Space Assemblies)				
Times Microwave	Approved			Size	CAGE CODE 68999		Drawing No.: IE-00418-XX		
Systems.				Α					
				Scale:	NA	Rev. ((A)	Sheet: 2 of 3	

	THE REVISION STATUS OF ALL SHEETS OF THIS DRAWING IS THE SAME AS SHEET 1								
REV	REV DESCRIPTION DATE BY								
Α	INITIAL RELEASE 10/28/22 YA								

IE-00418-04	Times Microwave Systems IBPS092-SMSM-12.0IN \$\$\$\$\$
IE-00418-04	

- 7.3 \$ = 5-digit Serial Number for this specific configuration.
- 7.4 Register to be Maintained for Serial Number.

8.0 NOTES

- 8.1 All Dimensions are in INCH.
- 8.2 Assemblies built in Class 100,000 clean room.
- 8.3 Low outgassing materials per ASTM E595.
- 8.4 Unless Otherwise Specified: Tolerance will be,

Linear Dimension	Tolerance
<20 INCH	±0.4 INCH
20-79 INCH	±0.6 INCH
>79 INCH	±0.8 INCH

^{**}Tolerances are not accumulative.

Unless otherwise specified, dimensions are in INCH. Tolerances are applicable when spec-	Ap	Approvals		_	TIMES MICROWAVE SYSTEMS				
ified.	Drawn	YA	10/28/22		www.timesmicrowave.com			crowave.com	
These drawings and specifications contain proprietary information	Checked			PT-092 CABLE ASSEMBLY				_	
which is the property of	Annroyed				(Space Assemblies)				
i imes iviicrowave	Approved			Size	CAGE CODE 68999		Drawing No.:		
Systems.				Α			IE.	-00418-XX	
				Scale:	NA	Rev. ((A)	Sheet: 3 of 3	