



# Sticklers Fiber Optic Splice & Connector Cleaner

## Product Features

- Fast evaporating, no residue optical grade cleaning fluid for cleaning fiber
- Not regulated for transport by land, sea, or air
- Nonflammable, nontoxic
- Dissipates electrostatic charges
- Compliant with Ventura County Air Pollution Control District Rule 74.6; reference 74.6; B.2.C
- ROHS and REACH compliant



## Typical Cleaning Applications

- Pigtails and bare fibers for fusion splicing
- Ribbon fibers for mass fusion splicing
- Splicing plastic optical fibers and connectors
- Ceramic and composite ferrules
- Most glass and plastic photonic lenses
- Suitable cleaning fluid for tool kits

Part Number: MCC-POCXXX



## Packaging

Packaging	3 oz (85 g) NET fluid weight	10 oz (284 g) NET fluid weight
Part Number	MCC- POC03M	MCC-POC10M
Cleans Per Can	650+	2500+
Can Specifications	- 4.23 oz (120 g) total can weight - 1.54" OD x 5.12" H (39 mm OD x 130 mm H)	- 13.2 oz (374 g) total can weight - 2.6" OD x 6.75" H (66 mm OD x 172 mm H)
Case Dimensions	8" L x 6" W x 6" H (203 mm L x 152 mm W x 152 mm H)	12" L x 9" W x 7" H (305 mm L x 229 mm W x 178 mm H)
Case Quantity	12 Cans per Case	12 Cans per Case
GHS/HCS Pictogram	Not Applicable	Not Applicable
Recycle Symbol		



We meet or exceed customer expectations in product quality and on time delivery



## Sticklers Fiber Optic Splice & Connector Cleaner conforms to the following Fiber Optic Industry Standards:

Industry Standards	Section	Description
ANSI/TIA 455-240 2009		Fiber Optic Connector End-Face Cleaning Evaluation liquid
ANSI/TIA 568.3D-2016	E.3.5	Connector End-Face Cleaning
ARINC 805-4		Fiber Optica Test Procedures
ARINC 806-5		Fiber Optic Installation & Maintenance
AT&T ATT-TP-76461		Inspecting & Cleaning End-Faces
Cisco Systems Doc: 51837		Inspecting & Cleaning Procedures for Fiber Connectors
IBM SY27-2597-15		Cleaning End-Faces for Maintaining Fibr Links
IEC 61300-3-35	5.3	End-Face Cleaning
IEC 61627-1	7.8	Acceptable Wet-Dry Cleaning
IEC 62627-1	9.3	Procedure Wet-Dry Cleaning w/ Reel Type Cleaners
IEC 61627-1	9.4	Procedure West-Dry Cleaning w/ Sticks & Clickers
IPC 8497-1	7.3.6	Cleaning Fluids & West Swabs & Face Cleaning
IPC 8497-1	10	Minimizing Electrostatic Charge Effect
NASA-STD 8739.5A	8	Cleaning Workmanship Standards
SAE AIR6031		End-Face Cleaning
SAE ARP 6283	8.6	Approved Cleaning Solvents
SAE ARP 6283	9.1.1	Wet-Dry Cassette Cleaning
Telcordia GR2923 CORE Issue 2		End-Face Cleaning
Telcordia GR765-CORE	4.6	Fusion Splicing Materials & Consumables Criteria
Verizon VZ.TRP.9461	5.0	End-Face Cleaning

## Ordering Information

MCC-POC

XXX

**NET fluid weight**

03M = 3 oz (85 g)

10M = 10 oz (284 g)

03GL = 33 oz (1 kg)

03GG = 1 gal (4.54 kg)

Rev. 01 Initial Release: RP  
Rev. 02 Ordering Information added: RP



We meet or exceed customer expectations in product quality and on time delivery

