CHANGE NOTIFICATION



May 29, 2014

Dear Sir/Madam: PCN# 052914

Subject: Notification of Additional Assembly Location, ASE Korea for LTM4600/LTM4602

Please be advised that Linear Technology has successfully qualified ASE Korea as an assembly site for the subject devices. It was desirable to qualify ASE Korea to serve as an alternate source since it is located in a different geographic area than our existing assembly location in Penang, Malaysia. ASE Korea is ISO9002, QS9000, ISO14001, TS16949, OHSAS 18001 and QC80000 certified. A summary of ASE Korea's product mix and LTC's qualification results are shown on the attached pages. The facility passed a site audit by LTC's supplier quality organization. LTC product assembled in ASE Korea can be identified by the country of origin marked on the device as "KR". The product photos showing the ASE Korea marking are attached. The datecode of the first units assembled by ASE Korea will be approximately 1407. The list of affected part numbers is presented below in the table.

Part Number	Part Marking	Package Type
LTM4600EV#PBF	LTM4600EV	LGA
LTM4600IV#PBF	LTM4600IV	LGA
LTM4600HVEV#PBF	LTM4600HVEV	LGA
LTM4600HVIV#PBF	LTM4600HVIV	LGA
LTM4602IV#PBF	LTM4602V	LGA
LTM4602EV#PBF	LTM4602V	LGA
LTM4602HVIV#PBF	LTM4602HVV	LGA
LTM4602HVEV#PBF	LTM4602HVV	LGA

Additionally, Linear Technology performs reliability testing on production lots in accordance with our Quick Reaction Reliability (QR2) Monitor Program. This monitor program is designed to provide fast feedback for possible reliability problems associated with package assembly. Please provide an expeditious approval to this PCN, so that LTC can build subject packages at ASE.

Should you have any concerns, please contact me before July 30, 2014, at which time we will consider this change to be approved. If you have any questions or concerns, please feel free to contact me at (408) 432-1900 ext. 2077 or by e-mail at JASON.HU@LINEAR.COM.

Sincerely,

Jason Hu Quality Assurance Engineer

ASE Korea Capacity Summary

ASE Korea 76, Saneopdanji-gil, Paju-si, Gyeonggi-do, Korea

Tel: 82-31-9400-114, 82-31-9400-539


Head counts: 2,791

Package Portfolio - Breakdown ** ASE GROUP



- Analog Power for Automotive
- RF for digital/consumer
- MEMS for safety
- Array Packages

2013 Production Mix by Package




Quality System Certification



- ISO9002 certified by SGS-Yarsely in December 1993.
- QS9000 certified by LRQA in June 1997
- ISO14001 certified by LRQA in October 1999
- TS16949 certified by LRQA in August 2003
- OHSAS18001 certified by KFQ in September 2005
- Sony Green Partner certified by Sony in August 2007
- QC80000 certified by SGS in November 2007

*Surveillance Audit: Every 6 Months



Country of Origin on Top Mark





LTM4600HVEV

µModule

149345 = 1407KR



LTM4602V

µModule

149351 = 1407KR





0

153.50

PACKAGE RELIABILITY DATA LTM4600/LTM4602 ASE ASSEMBLY SITE QUALIFICATION

5/7/2014

• J-STD-020 MSL 3 PRECONDITIONING: 192h +30°C/60%R.H. SOAK, 3x REFLOW AT +245°C PEAK

DEVICE TYPE	SAMPLE SIZE	OLDEST DATE CODE	NEWEST DATE CODE		OF FAILURES	
LTM4600	462	1407	1407		0	
LTM4602	461	1407	1407		0	
	923				0	
• TEMP CYCLE FROM -55°C to +125°C (1)						
DEVICE TYPE	SAMPLE SIZE	OLDEST DATE CODE	NEWEST DATE CODE	K DEVICE CYCLES	NUMBER OF FAILURES	
LTM4600	154	1407	1407	77.00	0	
LTM4602	153	1407	1407	76.50	0	

THERMAL SHOCK FROM -55°C to +125°C (1)

154

DEVICE TYPE	SAMPLE SIZE	OLDEST DATE CODE	NEWEST DATE CODE	K DEVICE CYCLES	NUMBER OF FAILURES
LTM4600	154	1407	1407	77.00	0
LTM4602	154	1407	1407	77.00	0
	154			154.00	0

⁽¹⁾ Environmental stress are preceded by J-STD-020 Level 3 Preconditioning: 192h 30°C/60% R.H. soak, followed by 3x Reflow at 245°C